

#### SPECIFICATION

TO ALL WHOM IT MAY CONCERN:

BE IT KNOWN THAT WE, JUNICHI HARA, a citizen of Japan residing at Kanagawa, Japan, TAKU KODAMA, a citizen of Japan residing at Kanagawa, Japan and SHOUSA KU TOKUDA, a citizen of Japan residing at Tottori, Japan have invented certain new and useful improvements in

#### IMAGE PROCESSING DEVICE

of which the following is a specification:-

## BACKGROUND OF THE INVENTION

### 1. Field of the Invention

The present invention relates to an image processing device, an image forming apparatus, a  
5 program, and a storage medium.

### 2. Description of the Related Art

In the conventional technique of editing images compressed by the JPEG algorithm, in order to  
10 edit a compressed image, the whole compressed image has to be decoded first to obtain the original uncompressed image, and then the uncompressed image is edited. This technique requires a relatively large memory capacity, and is difficult to achieve high speed image processing.

15 To solve the problem, techniques have been proposed to index sections of an image compressed by the JPEG algorithm. For example, Japanese Laid Open Patent Application No. 6-46243 and Japanese Laid Open Patent Application No. 7-170390 disclose such  
20 techniques.

However, techniques disclosed in Japanese Laid Open Patent Application No. 6-46243 and Japanese Laid Open Patent Application No. 7-170390 require special devices for dealing with data generated by DPCM  
25 (differential Pulse Coding Modulation) in JPEG. This

results in a complicated configuration of the system,  
and high manufacturing cost.

SUMMARY OF THE INVENTION

5           Accordingly, it is a general object of the  
present invention to solve one or more problems of the  
related art.

          A specific object of the present invention  
is to provide an image processing device capable of  
10   increasing processing speed with a simple configuration  
and without increasing required memory capacity when  
editing a compressed image.

          According to a first aspect of the present  
invention, there is provided an image processing device,  
15   comprising: an image dividing unit configured to divide  
an input image into a plurality of image sections; an  
encoding unit configured to independently encode each  
of the image sections, and generate a first code stream  
including a plurality of code sections corresponding to  
20   the image sections; and an editing unit configured to  
edit one of the code sections in the first code stream,  
and generate a second code stream based on the edited  
code section.

          According to the present invention, because  
25   the input image is divided into independent image

sections, and these image sections are encoded independently, it is possible to independently edit any code section corresponding to an image section without decoding the code section or the whole code stream, and  
5 it is not necessary to use any special devices. As a result, it is possible to increase processing speed with a simple configuration and without increasing memory capacity.

The editing unit may include a deletion unit  
10 configured to delete at least one of the code sections from the first code stream and output the second code stream including the remaining code sections in the first code stream. Further, the deletion unit may allocate information data indicating that the deleted  
15 code section is out of the input image to a header of the deleted code section, and output the second code stream including the remaining code sections in the first code stream and the deleted code section.

In addition, the editing unit may include an  
20 extraction unit configured to extract at least one of the code sections from the first code stream and output the second code stream including the extracted at least one code section. Further, the extraction unit may allocate information data indicating that each of the  
25 unextracted code sections is out of the input image to

a header of each of the unextracted code sections, and output the second code stream including the extracted code section and the unextracted code sections.

In addition, the editing unit may include a  
5 selection unit configured to select at least one of the code sections from the first code stream, and a replacement unit configured to replace the selected code section with predetermined coded data and output  
the second code stream including the unselected code  
10 sections in the first code stream and the predetermined coded data. Further, the predetermined coded data may include a plurality of pixels each having a predetermined pixel value.

According to the present invention, it is  
15 possible to perform editing such as deletion, extraction, and replacement of individual image sections and output various kinds of code streams.

The editing unit may further include a  
decoding unit configured to decode the selected code  
20 section and generate first image data corresponding to the selected code section; an image data generation unit configured to generate second image data based on the first image data; and a compression unit configured to encode the second image data and generate coded data,  
25 and output the coded data to the replacement unit as

the predetermined coded data.

The editing unit may further include a detection unit configured to determine a texture pixel value of the first image data output from the decoding unit; and the image data generation unit assigns the determined texture pixel value to pixels of the first image data and outputs the assigned first image data as the second image data.

According to the present invention, it is possible to modify a part of the input image by extracting, decoding and editing an individual image section, generating a new image section and inputting the new image section to the input image. For example, the pixels of the extracted image section may be modified to have other values, such as the value of the texture portion of the input image. In doing this, it is possible to naturally delete an image section or to extract an image section without leaving a hole in the input image.

The replacement unit may replace image data of the selected code section with image data of the predetermined coded data and maintains a header of the selected code section unchanged. Alternatively, the replacement unit may replace a header and image data of the selected code section with a header and image data

of the predetermined coded data, respectively. Further,  
when replacing the selected code section with the  
predetermined coded data, the replacement unit replaces  
a data length of the selected code section or a data  
5 length of image data of the selected code section with  
a data length of the predetermined coded data or a data  
length of image data of the predetermined coded data.

As an embodiment of the present invention,  
the encoding unit may encode each of the image sections  
10 by using one of entropy coding with two-dimensional  
discrete wavelet transformation and arithmetic coding.  
Further, the encoding unit may encode each of the image  
sections by using the JPEG 2000 algorithm; and each of  
the image sections corresponds to a tile in the JPEG  
15 2000 algorithm. In this case, the height and the width  
of the tile are multiples of a quantity  $d = 2^L$ , where  $L$   
is the wavelet decomposition level.

According to the present invention, it is  
possible to edit each individual tile without being  
20 affected by wavelet division.

According to a second aspect of the present  
invention, there is provided an image forming apparatus  
including an image reading unit configured to read an  
image on a manuscript; an image processing device,  
25 comprising an image dividing unit configured to divide

an input image into a plurality of image sections; an encoding unit configured to independently encode each of the image sections, and generate a first code stream including a plurality of code sections corresponding to the image sections; and an editing unit configured to edit one of the code sections in the first code stream, and generate a second code stream based on the edited code section; and a printer engine configured to form an image on a sheet of paper based on the second code stream.

According to a third aspect of the present invention, there is provided a program executed by a computer for processing an input image, comprising the steps of: dividing the input image into a plurality of image sections; independently encoding each of the image sections, and generating a first code stream including a plurality of code sections corresponding to the image sections; and editing one of the code sections in the first code stream, and generating a second code stream based on the edited code section.

According to a fourth aspect of the present invention, there is provided a storage medium that stores a program executed by a computer for processing an input image, the program comprising the steps of: dividing the input image into a plurality of image



sections; independently encoding each of the image sections, and generating a first code stream including a plurality of code sections corresponding to the image sections; and editing one of the code sections in the  
5 first code stream, and generating a second code stream based on the edited code section.

These and other objects, features, and advantages of the present invention will become more  
10 apparent from the following detailed description of preferred embodiments given with reference to the accompanying drawings.

#### BRIEF DESCRIPTION OF THE DRAWINGS

15 FIG. 1 is a block diagram of an image processing device according to a first embodiment of the present invention;

FIG. 2 is a functional block diagram of the image processing device 1;

20 FIG. 3 is a diagram illustrating an example of dividing an image into tiles;

FIG. 4 is a data diagram illustrating an example of the structure of a code stream 31 generated by encoding the tiles shown in FIG. 3;

25 FIG. 5 is a schematic diagram showing

operation of deleting tiles from a code stream;

FIG. 6 is a data diagram illustrating the code stream 37 after deletion of tiles from the code stream 31;

5           FIG. 7 is a schematic diagram showing operation of extracting tiles from a code stream;

FIG. 8 is a data diagram illustrating the code stream 38 formed by tiles extracted from the code stream 31;

10           FIG. 9 is a schematic diagram showing a configuration for executing the operation of replacing tiles in a code stream with other data;

FIG. 10 is a data diagram illustrating the code stream 39 generated after replacing tiles in the  
15 code stream 31;

FIG. 11 is a block diagram showing another configuration for executing the operation of replacing tiles in a code stream;

FIGS. 12A through 12C are tiled images  
20 illustrating image processing by the configuration shown in FIG. 11;

FIG. 13 is a block diagram showing still another configuration for executing the operation of replacing tiles in a code stream;

25           FIG. 14 is a block diagram showing a

configuration of an image forming apparatus according to a second embodiment of the present invention;

FIG. 15 is a block diagram showing a hardware configuration of a portion of the image processing unit 54; and

FIG. 16 is a flow chart showing the operation of the digital copy machine 51 when editing a code stream of an image.

#### 10 DESCRIPTION OF THE PREFERRED EMBODIMENTS

Below, preferred embodiments of the present invention are explained with reference to the accompanying drawings.

#### 15 First Embodiment

FIG. 1 is a block diagram of an image processing device according to a first embodiment of the present invention.

The image processing device 1 illustrated in FIG. 1, for example, is a computer that includes a CPU 2 that performs various calculations and controls parts of the image processing device 1; a memory 3 including, for example, ROM (Read Only Memory) and RAM (Randomly Access Memory); a storage device 5 such as a hard disk; 25 an input device 6 such as a mouse and a keyboard; a

display 7 such as an LCD (Liquid Crystal Display) and a  
CRT (Cathode Ray Tube); a storage medium 8 such as an  
optical disk; a storage medium reading device 9 for  
reading the storage medium 8; and a communication  
5 interface (I/F) 11.

A bus 4 is provided to connect the CPU 2,  
memory 3, storage device 5, input device 6, display 7,  
the storage medium reading device 9, and I/F 11. The  
image processing device 1 is connected to a network 10,  
10 for example, the Internet, through I/F 11.

In addition to an optical disk 8, such as a  
CD and a DVD, the storage medium 8 may also be any of a  
Magneto-optic disk (MO), a flexible disk, or any other  
recording medium. According to the specific type of the  
15 storage medium 8, the storage medium reading device 9  
may be an optical disk drive, an MO drive, a flexible  
disk drive, and so on.

An image processing program for realizing  
the functions provided by the present invention is  
20 stored in the storage device 5. This image processing  
program may be read from the storage medium 8 by using  
the storage medium reading device 9, and installed in  
the storage device 5, or may be downloaded through the  
network 10 and installed in the storage device 5. After  
25 installing this image processing program in the storage

device 5, the image processing device 1 becomes operable. This image processing program may be an independent application program, or a part of an application package; it can be made specific to a certain OS or be independent of the OS.

FIG. 2 is a functional block diagram of the image processing device 1.

As shown in FIG. 2, functionally, the image processing device 1 includes an image divider 21, an encoder 22, and an editor 23.

The image divider 21 divides an image into a number of small image sections, in other words, the image divider 21 divides image data into a series of small image data sections, and outputs the data section series to the encoder 22.

The encoder 22 encodes each of the small image sections independently, thereby compressing the input image data and generating a code stream. In this coding processing, for example, the JPEG 2000 algorithm is used, and entropy coding with two-dimensional discrete wavelet transformation or arithmetic coding is used for encoding the input image data. Hence, the above "small image section", the unit division of the input image data, is equivalent to the so-called "tile" in JPEG 2000.

The editor 23 edits each tile in the code stream generated in the encoder 22, and generates a new code stream.

The functions of the image divider 21, the encoder 22, and the editor 23 are realized by an image processing program executed by the CPU 2.

When using the JPEG 2000 algorithm, assuming  $L$  represents the level of wavelet division, and  $d = 2^L$ , if the width and height of the tile are multiples of  $d$ , the size of the tile is not influenced by the wavelet division, and hence it is possible to edit each tile independently.

Below, processing by the editor 23 is described in detail.

FIG. 3 is a diagram illustrating an example of dividing an image into tiles. As shown in FIG. 3, the image divider 21 divides an input image into 16 tiles (T00 through T15). The encoder 22 encodes the 16 tiles separately, and the editor 23 edits the thus generated code streams.

FIG. 4 is a diagram illustrating an example of the structure of a code stream 31 generated by encoding the tiles shown in FIG. 3. As illustrated in FIG. 4, the code stream 31 has a main header 32 at the beginning, an EOC (End Of Code stream) 33 at the end,

and 16 tiles 36 allocated and between the main header 32 and the EOC 33. Each of the tiles 36 is formed from a tile header 34 and a bit stream 35, and these tiles 36 are arranged in order of the tile number.

5 [Deletion of tiles]

FIG. 5 is a diagram showing an operation of deleting tiles from a code stream. As shown in FIG. 5, the editor 23 has a deletion unit 41. The deletion unit 41 deletes one or more tiles 36 from the code stream 31,  
10 and the remaining coded data form a new code stream 37.

FIG. 6 is a diagram illustrating the code stream 37 after deletion of tiles from the code stream 31. As shown in FIG. 6, the tile 10 is deleted from the code stream 31, resulting in the code stream 37.

15 Specifically, the deletion unit 41 reads the tile numbers of the tiles 36 in the code stream 31 input to the editor 23, deletes the tile 10 from the code stream 31 as specified, and outputs the remaining coded data as the code stream 37. Because the coded  
20 data corresponding to each of the tiles 36 are independent, the tiles 36 that are not deleted are unchanged, that is, the undeleted tiles 36 are the same in the code stream 31 and in the code stream 37. Therefore, to generate the code stream 37, the coded  
25 data in the code stream 31 can be used directly. It is

not necessary to encode any new data; consequently,  
high speed image processing is enabled.

In FIG. 6, it is shown that after deletion  
of the tile 10 from the code stream 31, the tile 10 is  
5 not allocated in the new code stream 37. As an  
alternative, the tile 10 may also be allocated in the  
code stream 37, in which case the index of the tile 10,  
serving as the position data of the tile 10, is  
modified to a value not used by the system, so as to  
10 set the tile 10 out of the region of the input image.  
In doing so, the deleted tile will not be displayed  
even when it is decoded. Furthermore, by allocating the  
deleted tiles in the new code stream 37, it is possible  
to recover the original code stream 31 from the code  
15 stream 37.

#### [Extraction of tiles]

FIG. 7 is a diagram showing an operation of  
extracting tiles from a code stream. As shown in FIG. 7,  
20 the editor 23 has an extraction unit 42. The extraction  
unit 42 extracts one or more tiles 36 from the code  
stream 31; and the extracted coded data form a new code  
stream 38.

FIG. 8 is a diagram illustrating the code  
25 stream 38 formed by tiles extracted from the code



stream 31. As shown in FIG. 8, the tile 10 is extracted from the code stream 31, and the tile 10 forms the code stream 38.

Specifically, the extraction unit 42 reads  
5 the tile numbers of the tiles 36 in the code stream 31 input to the editor 23, extracts the tile 10 from the code stream 31 as designated, and outputs the extracted coded data as the code stream 38. Because the coded data corresponding to each of the tiles 36 are  
10 independent, the extracted coded data in the code stream 38 are the same as the coded data of the tile 10 in the code stream 31. That is, to generate the code stream 38, the coded data in the code stream 31 can be used directly, and it is not necessary to encode any  
15 new data; therefore, it is possible to perform high speed image processing.

Similar to the aforesaid deletion processing, in addition to the tile 10, other unextracted tiles in the code stream 31 may also be allocated in the code  
20 stream 38, but the indices of these tiles, serving as the position data of the tiles, are modified to values not used by the system, so as to set these tiles out of the region of the input image. In doing so, these unextracted tiles will not be displayed even though  
25 they are decoded. Furthermore, by allocating the

unextracted tiles in the new code stream 38, it is possible to recover the original code stream 31 from the code stream 38.

5 [Replacement of tiles]

FIG. 9 is a diagram showing a configuration for executing the operation of replacing tiles in a code stream with other data. As shown in FIG. 9, the editor 23 has a selection unit 43 and a replacement  
10 unit 44. The selection unit 43 selects one or more tiles from the code stream 31, and the replacement unit 44 replaces the selected tiles with other coded data, and outputs a new code stream 39.

FIG. 10 is a diagram illustrating the code  
15 stream 39 generated after replacing tiles in the code stream 31. As shown in FIG. 10, coded data of the tile 10 in the code stream 31 is selected and replaced with coded data of a tile 10', resulting in the code stream 39.

20 For example, the coded data of the tile 10' may be coded data of a prepared image compressed by using the JPEG 2000 algorithm. Each pixel in the prepared image may be assigned any value, for example, data indicating white color (in the case of 8 bit pixel  
25 data, the possible value ranges from 0 through 255, and

white color is equivalent to 0) may be assigned and encoded, or data indicating the texture of the original image represented by the code stream 31 may also be assigned to pixels in the prepared image.

5           It should be noted that when the replacement unit 44 replaces the selected tiles with other coded data, the replacement unit 44 may replace both the tile header 34 and the bit stream 35 of the selected tiles, or just replace the bit stream 35, because it is  
10   sufficient for image editing. In the latter case, however, since length of the tile header 34 or the bit stream 35 may change, length of the tile header 34 or the bit stream 35 should be rewritten.

FIG. 11 is a block diagram showing another  
15   configuration for executing the operation of replacing tiles in a code stream. As shown in FIG. 11, the editor 23 may include the selection unit 43, a decoder 45, an image data generating unit 46, a compressing unit 47, and the replacement unit 44.

20           The selection unit 43 selects one or more tiles from the code stream 31, the decoder 45 decodes the selected tiles, the image data generating unit 46 generates new image data based on the image data of the decoded tiles, the compressing unit 47 encodes and  
25   compresses the new image data by using the JPEG 2000

algorithm, and the replacement unit 44 replaces the selected tiles with the coded data output from the compressing unit 47, and outputs a new code stream 60.

In this configuration, the image data  
5 generating unit 46 may have various tools for processing image data, enabling a user to edit the selected tiles in any desired way.

FIGs. 12A through 12C are views illustrating image processing by the configuration shown in FIG. 11.  
10 As shown in FIG. 12A, an original image is divided into 16 tiles represented by T00 through T15 in order, similar to FIG. 3. As shown in FIG. 12B, the tile 10 is selected from the original image, and the image of the tile 10 is edited by a user in the way described above,  
15 and this generates a new image, corresponding to the tile 10'.

In FIG. 12C, the tile 10 in the original image is replaced by the tile 10', forming a new image as shown in FIG. 12C corresponding to the code stream  
20 60.

FIG. 13 is a block diagram showing still another configuration for executing the operation of replacing tiles in a code stream. As shown in FIG. 13, the editor 23 may include the selection unit 43, the  
25 decoder 45, a texture detection unit 48, the image data

generating unit 46, the compressing unit 47, and the replacement unit 44.

The selection unit 43 selects one or more tiles from the code stream 31, and the decoder 45  
5 decodes the selected tiles. The texture detection unit 48 detects pixel values of the texture portion in the image obtained by decoding the selected tiles. For example, the texture detection unit 48 counts the pixel values of the pixels in the selected image, and  
10 determines the pixel value that appears most frequently to be the pixel value of the texture portion. The image data generating unit 46 generates a new image in which the pixel values of all pixels are set to the determined texture pixel value. The compressing unit 47  
15 encodes and compresses the new image data by using the JPEG 2000 algorithm, and the replacement unit 44 replaces the selected tiles with the coded data output from the compressing unit 47, and outputs a new code stream 61.

20

#### Second Embodiment

FIG. 14 is a block diagram showing a configuration of an image forming apparatus according to an embodiment of the present invention.

25 The image forming apparatus 51 shown in FIG.

14, for example, is a digital copy machine, and includes an image reading unit 52 such as a scanner, an image data control unit 53, an image processing unit 54, an image data storage unit 55, an image data writing  
5 unit 56 equipped with a print engine, an operational panel 57, and a communication interface 58.

The image reading unit 52 irradiates light to a document and detects the light reflected by the document using a CCD (Charge Coupled Device), which  
10 converts the light to electrical signals, and digitalizes the electrical signals by an A/D converter.

The image data control unit 53 controls the other units. In addition, the image data control unit 53 has interfaces with the other units, and controls  
15 data transfer with the other units through the interfaces.

The image data storage unit 55 stores image data under instructions of the image data control unit 53.

20 The image data writing unit 56, controlled by the image data control unit 53, prints an image on a medium, such as a piece of paper, based on an input image. The image data writing unit 56 may print the image on the medium by means of, for example,  
25 electrophotography, inkjet, dye-sublimation heat

transfer, silver salt imaging, direct thermal printing, and thermal Wax transfer.

The operational panel 57 includes a keyboard for a user to conduct operations, and a display for  
5 presenting images or messages.

The communication interface 58 is used to connect the digital copy machine 51 with computers on the outside for data transfer between them.

The image processing unit 54 is formed from  
10 any image processing device as described in the first embodiment. It performs various processing on image data transmitted from the image reading unit 52 or the communication interface 58. For example, the image processing unit 54 encodes and compresses input image...  
15 data using the JPEG 2000 algorithm, and is capable of changing the image size, changing image positions, and so on.

FIG. 15 is a block diagram showing a hardware configuration of a portion of the image  
20 processing unit 54. As shown in FIG. 15, the image processing unit 54 includes a CPU 61, a ROM 62, and a RAM 63, and they are connected by the bus 64.

In the ROM 62 an image processing program is stored, and the CPU 61 executes the image processing  
25 program while using the RAM 63 as a working area

thereof to realize functions as illustrated by FIG. 2, FIG. 9, FIG. 11, and FIG. 13, generates code streams as described in the first embodiment, and edits thus generated code streams in various ways.

5               In the editing processing, the image processing unit 54 performs various processing on image data transmitted from the image reading unit 52 and the communication interface 58. For example, the image processing unit 54 encodes and compresses input image  
10 data using the JPEG 2000 algorithm, and stores the resultant code stream in the image data storage unit 55. When necessary, the image processing unit 54 reads out the code stream from the image data storage unit 55, and edits the code stream in various ways.

15               FIG. 16 is a flow chart showing the operation of the digital copy machine 51 when editing a code stream of an image.

                  In step S1, a user operates the operation panel 57 to input a command for reading in an image.

20               In step S2, image data are transmitted from the image reading unit 52 or the communication interface 58.

                  In step S3, the image is displayed on the display on the operation panel 57.

25               In step S4, tiles in the image are assigned



numbers, and the tiles are displayed together with the numbers. Then the user is queried whether image editing is to be performed. If image editing is to be performed, the routine proceeds to step S5. (Note: In FIG. 16 S5  
5 change "EDITION" to "EDITING".) If image editing is not to be performed, the routine proceeds to step S13.

In step S5, if the user desires to edit the image, the user is further queried about which kind of editing is to be performed. For example, the user is  
10 requested to choose one of image partial deletion, image partial extraction, and image partial replacement.

In step S6, if the user chooses partial deletion in step S5, the user further specifies the number(s) of the tile(s) to be deleted from the image  
15 on the display.

In step S7, if the user chooses partial extraction in step S5, the user further specifies the number(s) of the tile(s) to be extracted from the image on the display.

20 In step S8, if the user chooses partial replacement in step S5, the user further specifies the number(s) of the tile(s) to be replaced in the image on the display.

In step S9, the user specifies paper size to  
25 be used for printing the resultant image.

In step S10, the user pushes the execution button on the operational panel 57.

In step S11, depending on the choice made in step S5, one of image partial deletion, image partial  
5 extraction, and image partial replacement is executed to edit the input image. The details of these processes are described in the first embodiment, and are omitted here.

When replacing a part of the input image,  
10 there appears a hole (an area lacking image data) in the input image. This hole can be filled, for example, by embedding an image whose pixels have the value of the texture portion of the tiles to be replaced. The pixel value of the texture portion can be determined by  
15 the texture detection unit 48 in FIG. 13.

In step S12, after processing in step S11, the resultant code stream is stored in the image data storage unit 55.

In step S13, if image editing is not to be  
20 performed, as decided in step S4, the input image data are encoded and compressed by using JPEG 2000, and a code stream is generated. This code stream is also stored in the image data storage unit 55 in step S12.

In step S14, the code stream is transmitted  
25 to the image data writing unit 56, and the

corresponding image is printed on the paper of the specified size.

While the present invention is described with reference to specific embodiments chosen for purpose of illustration, it should be apparent that the invention is not limited to these embodiments, but numerous modifications could be made thereto by those skilled in the art without departing from the basic concept and scope of the invention.

10 Summarizing the effects of the present invention, because the input image is divided into image sections, and these image sections are encoded independently, it is possible to independently edit any code section corresponding to an image section without  
15 decoding the code section or the whole code stream, and it is not necessary to use any special devices. As a result, it is possible to increase processing speed with a simple configuration and without increasing memory capacity.

20 In addition, according to the present invention, it is possible to perform editing such as deletion, extraction, and replacement of an individual image section and obtain an output code stream.

Further, it is possible to modify a part of  
25 the input image by extracting, decoding and editing an

individual image section, generating a new image and putting the new image into the individual image section of the input image. For example, the pixels of the extracted image section may be modified to have other  
5 values, such as the value of the texture portion of the input image. In doing this, it is possible to naturally delete an image section or to extract an image section without leaving a hole in the input image.

Further, when the JPEG 2000 algorithm is  
10 used, according to the present invention, it is possible to edit each individual tile without being affected by wavelet division.

This patent application is based on Japanese  
Priority Patent Application No. 2002-273984 filed on  
15 September 19, 2002, the entire contents of which are hereby incorporated by reference.